

Anti-Static, High Temperature & Pneumatic Tyred Castors

Anti-Static & High Temperature Castors



A range of anti-static (electrically conductive) and high temperature castors. The anti-static wheels have pressed steel centres with black rubber tyres.

The High Temperature wheels are phenolic resin or high temperature rubber and have a range from -40°C to +280°C. Both ranges are available with and without brakes.

Castor Reference and Load Capacity

Wheel Diam.	Tread Width	Castor Type	Castor Height	Plate Size	Bolt Hole Spacing	Bolt Diam.	Swiv. Rad.	Anti Static Rubber	High Temp. Phenolic	High Temp. Rubber
3" + 80mm	TH=35mm	Swivel	108mm	105 x 85mm	80 x 60mm	8mm	75mm	-	80-3360-TH 100kg	-
		Fixed	108mm	99 x 85mm	80 x 60mm	8mm	-	-	80-3368-TH 100kg	-
4" 100mm	AS=22mm TH=35mm HT=34mm	Swivel	128mm	105 x 85mm	80 x 60mm	8mm	85mm	100-3360-ASR 70kg	100-3360-TH 125kg	100-3360-HT 60kg
		Fixed	128mm	101 x 85mm	80 x 60mm	8mm	-	100-3368-ASR 70kg	100-3368-TH 125kg	100-3368-HT 60kg
5" 125mm	AS=27mm TH=35mm	Swivel	155mm	105 x 85mm	80 x 60mm	8mm	105mm	125-3360-ASR 100kg	125-3360-TH 150kg	-
		Fixed	155mm	101 x 85mm	80 x 60mm	8mm	-	125-3368-ASR 100kg	125-3368-TH 150kg	-
6" + 160mm	AS=24mm TH=40mm	Swivel	200mm	137 x 105mm	105 x 80mm	10mm	140mm	160-3360-ASR 135kg	160-3360-TH 250kg	-
		Fixed	200mm	137 x 115mm	105 x 80mm	10mm	-	160-3368-ASR 135kg	160-3368-TH 250kg	-
8" 200mm	AS=30mm TH=50mm	Swivel	240mm	137 x 105mm	105 x 80mm	10mm	165mm	200-3360-ASR 205kg	200-3360-TH 300kg	-
		Fixed	240mm	137 x 115mm	105 x 80mm	10mm	-	200-3368-ASR 205kg	200-3368-TH 300kg	-

OPTIONAL EXTRA



Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix '**SWB**' to the swivel castor reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.

- 80mm wheels: increased by 45mm
- 100mm wheels: increased by 40mm
- 125mm wheels: increased by 30mm
- 160mm wheels: increased by 30mm
- 200mm wheels: increased by 20mm

Pneumatic Tyred Castors

Swivel and Fixed Pneumatic tyred castors. Available in 8" and 10" diameters.

Ideal for cushioning sensitive loads. The 10" wheel is used on cricket wicket covers as the wide tread prevents damage to the playing surface. Black tyres on grey metal centres.

Castor Reference and Load Capacity



Wheel Diam.	Tread Width	Castor Type	Castor Height	Plate Size	Bolt Hole Spacing	Bolt Diam.	Swiv. Rad.	8" Ref.	10" Ref.
8" 200mm	48mm	Swivel	240mm	137 x 105mm	105 x 80mm	10mm	165mm	200-3360-PWR 75kg	-
8" 200mm		Fixed	240mm	140 x 115mm	105 x 80mm	10mm	-	200-3368-PWR 75kg	-
10" 260mm	85mm	Swivel	302mm	200 x 160mm	105 x 115mm	12mm	215mm	-	260-3360-PWR 200kg
10" 260mm		Fixed	302mm	200 x 160mm	105 x 115mm	12mm	-	-	260-3368-PWR 200kg