

# Institutional Castors

## 314 Series

Size: 50mm, 75mm & 100mm

Light duty pressed steel swivel castors with flat top plates. Available in grey non-marking Rubber Tyred or Black Polypropylene wheels. Suitable for a wide range of light duty applications.



### Castor Reference and Load Capacity



Wheel Diam.	Tread Width	Plated Finish	Castor Height	Swivel Radius	Plate Size	Bolt Diam.	Grey Rubber	Black Polypropylene
2" 50mm	22mm	Zinc	72mm	45mm	60mm x 60mm 48/38 x 48/38	6mm	50-314-R 60kg	50-314-P 65kg
3" 75mm	*23mm	Zinc	101mm	68mm	60mm x 60mm 48/38 x 48/38	6mm	75-314-R 70kg	75-314-P 75kg
4" 100mm	*26mm	Zinc	124mm	75mm	60mm x 60mm 48/38 x 48/38	6mm	100-314-R 80kg	100-314-P 85kg

\* The 3" and 4" Polypropylene wheels have 22mm tread widths

**3" ANTI-STATIC WHEELS AVAILABLE TO SPECIAL ORDER**

## OPTIONAL EXTRA

### Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

### Swivel Radius

The swivel radius is increased when brakes are fitted.

- 50mm wheels: increased by 40mm
- 75mm wheels: increased by 32mm
- 100mm wheels: increased by 25mm

