

# Institutional Castors

## 314 Series

Size: 50mm, 75mm & 100mm

Light duty pressed steel swivel castors with flat top plates. Available in grey non-marking Rubber Tyred or Black Polypropylene wheels. Suitable for a wide range of light duty applications.



### Castor Reference and Load Capacity



Wheel Diam.	Tread Width	Plated Finish	Castor Height	Swivel Radius	Plate Size	Bolt Diam.	Grey Rubber	Black Polypropylene
2" 50mm	22mm	Zinc	72mm	45mm	60mm x 60mm 48/38 x 48/38	6mm	50-314-R 60kg	50-314-P 65kg
3" 75mm	*23mm	Zinc	101mm	68mm	60mm x 60mm 48/38 x 48/38	6mm	75-314-R 70kg	75-314-P 75kg
4" 100mm	*26mm	Zinc	124mm	75mm	60mm x 60mm 48/38 x 48/38	6mm	100-314-R 80kg	100-314-P 85kg

\* The 3" and 4" Polypropylene wheels have 22mm tread widths

**3" ANTI-STATIC WHEELS AVAILABLE TO SPECIAL ORDER**

## OPTIONAL EXTRA

### Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix ' SWB ' to the swivel castor reference.

### Swivel Radius

The swivel radius is increased when brakes are fitted.

50mm wheels: increased by 40mm

75mm wheels: increased by 32mm

100mm wheels: increased by 25mm

