

# Pneumatic & Trolley Wheels



## PD Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
6" (150mm)	39mm	30kg	38mm	1/2"	PD-6
7" (180mm)	45mm	50kg	38mm	1/2"	PD-7
8" (200mm)	45mm	50kg	38mm	1/2"	PD-8

*"Light duty wheels - tough moulded polypropylene centres fitted with ribbed tyres. PD range is specially designed for grass cutting machines and other light horticultural applications."*



## ABC Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
80mm	21mm	30kg	37mm	8mm	A-80
100mm	24mm	35kg	35mm	10mm	A-100
125mm	31mm	50kg	44mm	15mm	A-125
160mm	40mm	100kg	44mm	20mm	AB-160
200mm	33mm	130kg	44mm	20mm	AB-200L

*"Traditional light industrial range of wheels. The centres are black polypropylene with black rubber tyres."*



## EPR Series

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
6" (160mm)	30mm	150kg	51mm	3/4"	EPR-6 (3/4")
6" (160mm)	30mm	150kg	51mm	1"	EPR-6 (1")
8" (200mm)	30mm	200kg	51mm	3/4"	EPR-8 (3/4")
8" (200mm)	30mm	200kg	51mm	1"	EPR-8 (1")
10" (250mm)	60mm	275kg	51mm	1"	EPR-10 (1")
11" (270mm)	60mm	150kg	59mm	1"	EPR-11 (1")

*"Light industrial range of cushion tyred wheels having red centres with black tyres. Ideally suited for sack trucks and trolleys etc. Alternative diameters and hub bores available."*

*We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.*



## GB Series (Sandhopper)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
10 5/8" (270mm)	98mm	125kg	56mm	1"	GB-270 (1")

*"Extra wide tread wheels. Suitable for barrows, launching trolleys and any outdoor application."*

*We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.*



## PW Series (Plastic Centres)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Wheel Reference
8 3/4" (220mm)	65mm	100kg	76mm	1"PB	PW-250-4-25.4-76
10 1/4" (260mm)	85mm	120kg	76mm	1"PB	PW-300-4-25.4-76
10 1/4" (260mm)	85mm	120kg	76mm	1"RB	PWR-300-4-25.4-76
16" (400mm)	100mm	150kg	68mm	1"PB	PW-400-8-25.4-68
16" (400mm)	100mm	150kg	75mm	1"RB	PWR-400-8-25.4-75

*"Pneumatic tyred wheels suitable for low speed applications. Red centres with black tyres 4 ply rating."*

*We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.*



## PW Series (Puncture Proof)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Wheel Reference
10 1/4" (260mm)	85mm	120Kg	75mm	20mm RB	PWR-250-4-20-76/PP
10 1/4" (260mm)	85mm	120Kg	75mm	1" RB	PWR-250-4-25.4-76/PP
16" (400mm)	105mm	180Kg	75mm	20mm RB	PWR-400-4-20-75/PP
16" (400mm)	105mm	180Kg	75mm	1" RB	PWR-400-4-25.4-75/PP

*"Black, puncture-proof lightweight micro-cellular polyurethane tyre on red polypropylene centre"*

*We can produce bushes for the hub bore, which will reduce the bore size to: 1/2" or 20mm. The hub lengths will then be increased by 8mm and the load capacity reduced by 50%.*



## PW Series (Metal Centres)

Wheel Diameter	Tread Width	Load Cap.	Hub Length	Hub Bore	Reference Plain
8" (200mm)	48mm	75kg	60mm	20mm	WAT-8RBM20
10 1/4" (260mm)	85mm	200kg	76mm	20mm	PWMR-300-4-20-76
10 1/4" (260mm)	85mm	200kg	76mm	1"RB	PWMR-300-4-25.4-76
*16" (400mm)	100mm	250kg	76mm	1"RB	PWMR-400-8-25.4-76

*"Pneumatic tyred wheels suitable for low speed applications. Grey Metal centres with black tyres 4 ply rating."*

\* The 16" diameter wheel has a red metal centre and is also available in black to special order.