

Rubber & High Temperature Wheels



PVR Series

Medium/Heavy Duty Rubber Tyred Wheels

Finish: Black/Black, Red centres on 5", 6" and 8" wheels.

Wheel Diam.	Tread Width	Load Cap.	Hub Length	Hub Bore	Ref. Plain	Ref. Roller
3" + 80mm	27mm	70kg	45mm	12-20mm	80-PVP-20mm	80-PVR-12mm
4" 100mm	23mm	80kg	45mm	12-20mm	100-PVP-20mm	100-PVR-12mm
5" 125mm	23mm	100kg	45mm	12-20mm	125-PVP-20mm	125-PVR-12mm
6" + 160mm	25mm	150kg	58mm	15-23mm	160-PVP-23mm	160-PVR-15mm
8" 200mm	33mm	200kg	58mm	15-23mm	200-PVP-23mm	200-PVR-15mm



GVR Series

Medium/Heavy Duty (non-marking) Rubber Tyred wheels

Finish: Grey/Black

Wheel Diam.	Tread Width	Load Cap.	Hub Length	Hub Bore	Ref. Plain	Ref. Roller
3" + 80mm	27mm	70kg	45mm	12-20mm	80-GVP-20mm	80-GVR-12mm
4" 100mm	23mm	80kg	45mm	12-20mm	100-GVP-20mm	100-GVR-12mm
5" 125mm	23mm	100kg	45mm	12-20mm	125-GVP-20mm	125-GVR-12mm
6" + 160mm	25mm	150kg	58mm	15-23mm	160-GVP-23mm	160-GVR-15mm
8" 200mm	33mm	200kg	58mm	15-23mm	200-GVP-23mm	200-GVR-15mm



RN Series

Heavy Duty Blue Elastic Rubber Tyred Wheels

Finish: Blue/Black

Wheel Diam.	Tread Width	Load Cap.	Hub Length	Hub Bore	Ref. Plain	Ref. Roller
3" + 80mm	36mm	150kg	40mm	12mm	-	80-RNB
4" 100mm	29mm	200kg	44mm	12mm	-	100 RNB
5" 125mm	34mm	250kg	44mm	12mm	-	125 RNB
6" + 160mm	40mm	350kg	60mm	20mm	-	160 RNB
8" 200mm	40mm	400kg	60mm	20mm	-	*200 RNB

The 8" diameter wheels are fitted with ball journals



TH Series

Heavy Duty phenolic resin, high temperature wheels.

Temp range from: -40°C + 280°C

Finish: Black

Wheel Diam.	Tread Width	Load Cap.	Hub Length	Hub Bore	Ref. Plain
3" + 80mm	35mm	100kg	40mm	12mm	80-TH
4" 100mm	35mm	125kg	40mm	12mm	100-TH
5" 125mm	35mm	150kg	40mm	12mm	125-TH
6" + 160mm	40mm	250kg	58mm	20mm	160-TH
8" 200mm	50mm	300kg	58mm	20mm	200-TH



HT Series

Heat Resisting Rubber Wheel. Fitted with precision ball bearings.

Temp range from: -30°C + 260°C

Finish: Red/Silver

Wheel Diam.	Tread Width	Load Cap.	Hub Length	Hub Bore	Ball Bearing
4" 100mm	34mm	60kg	38mm	12mm	100-HT