

Extra Heavy Duty Stainless Steel Castors



Castor Reference and Load Capacity



| Wheel Diam | Tread Width | Castor Type | Castor Height | Plate size | Bolt Hole Spacing | Bolt Diam. | Swivel Rad. | White Nylon |
|---------------|-------------|-------------|---------------|--------------|-------------------|------------|-------------|---------------------|
| 5" 125mm | 40mm | Swivel | 164mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | 118mm | HSS-125-NY 700Kg |
| | 40mm | Fixed | 164mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | | HSF-125-NY 700Kg |
| 6" + 160mm | 40mm | Swivel | 200mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | 135mm | HSS-160-NY 700Kg |
| | 40mm | Fixed | 200mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | | HSF-160-NY 700Kg |
| 8" 200mm | 50mm | Swivel | 240mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | 155mm | HSS-200-NY 800Kg |
| | 50mm | Fixed | 240mm | 140 x 110 mm | 105 x 80/75 mm | 10mm | | HSF-200-NY 800Kg |

OPTIONAL EXTRA



Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.

125mm wheels: increased by 74mm
160mm wheels: increased by 100mm
200mm wheels: increased by 100mm