

Light Duty Bolt Hole Stainless Steel Castors



Castor Reference and Load Capacity

Wheel Diam.	Tread width	Castor Type	Castor Height	Bolt Hole Diam.	Swivel Radius		
						Thermoplastic Rubber	Electro-conductive Rubber (Ball Journal)
60mm	22mm	Swivel	89mm	10mm	57mm	SSL-60-TPR/BH10 40Kg	SSL-60-ASR/BH10 40Kg
3" + 80mm	22mm	Swivel	109mm	10mm	70mm	SSL-80-TPR/BH10 50Kg	SSL-80-ASR/BH10 50Kg
4" 100mm	30mm	Swivel	134mm	12mm	92mm	SSL-100-TPR/BH12 80Kg	SSL-100-ASR/BH12 80Kg
5" 125mm	30mm	Swivel	162mm	12mm	106mm	SSL-125-TPR/BH12 100Kg	SSL-125-ASR/BH12 100Kg
6" 150mm	30mm	Swivel	188mm	12mm	123mm	SSL-150-TPR/BH12 100Kg	SSL-150-ASR/BH12 100Kg

OPTIONAL EXTRA



Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.
 60mm wheels: increased by 33mm
 80mm wheels: increased by 30mm
 100mm wheels: increased by 82mm
 125mm wheels: increased by 53mm
 150mm wheels: increased by 23mm