

Light Duty Flat Top Plate Stainless Steel Castors



Castor Reference and Load Capacity

Wheel Diam.	Tread width (mm)	Castor Type	Castor Height	Plate size (mm)	Bolt Hole spacing (mm)	Bolt Diam.	Swiv. Rad.		
								Thermoplastic Rubber	Electro-conductive Rubber (Ball Journal)
60mm	22mm	Swivel	89mm	65 x 50 mm	50 x 36 mm	6mm	57mm	SSL-60-TPR 40Kg	SSL-60-ASR 40Kg
	22mm	Fixed	89mm	65 x 54 mm	50 x 36 mm	6mm	-	SFL-60-TPR 40Kg	SFL-60-ASR 40Kg
3" + 80mm	22mm	Swivel	109mm	65 x 50 mm	50 x 36 mm	6mm	70mm	SSL-80-TPR 50Kg	SSL-80-ASR 50Kg
	22mm	Fixed	109mm	65 x 54 mm	50 x 36 mm	6mm	-	SFL-80-TPR 50Kg	SFL-80-ASR 50Kg
4" 100mm	30mm	Swivel	134mm	90 x 70 mm	70 x 50 mm	8mm	92mm	SSL-100-TPR 80Kg	SSL-100-ASR 80Kg
	30mm	Fixed	134mm	90 x 70 mm	70 x 50 mm	8mm	-	SFL-100-TPR 80Kg	SFL-100-ASR 80Kg
5" 125mm	30mm	Swivel	162mm	90 x 70 mm	70 x 50 mm	8mm	106mm	SSL-125-TPR 100Kg	SSL-125-ASR 100Kg
	30mm	Fixed	162mm	90 x 70 mm	70 x 50 mm	8mm	-	SFL-125-TPR 100Kg	SFL-125-ASR 100Kg
6" 150mm	30mm	Swivel	188mm	90 x 70 mm	70 x 50 mm	8mm	123mm	SSL-150-TPR 100Kg	SSL-150-ASR 100Kg
	30mm	Fixed	188mm	90 x 70 mm	70 x 50 mm	8mm	-	SFL-150-TPR 100Kg	SFL-150-ASR 100Kg

OPTIONAL EXTRA



Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.

- 60mm wheels: increased by 33mm
- 80mm wheels: increased by 20mm
- 100mm wheels: increased by 82mm
- 125mm wheels: increased by 53mm
- 150mm wheels: increased by 23mm