

# Medium Duty Bolt Hole Stainless Steel Castors



Castor Reference and Load Capacity



| Wheel Diam. | Tread width (mm)                                       | Castor Type | Castor Height | Swivel Race Diam | Bolt Diam. | Swiv. Rad. | Grey Rubber              | Polyurethane             | White Nylon              | High Temp Termotex      | High Temp Rubber       |
|-------------|--|-------------|---------------|------------------|------------|------------|--------------------------|--------------------------|--------------------------|-------------------------|------------------------|
| 3" + 80mm   | GVR = 27<br>PNB = 38<br>NY = 34<br>TH = 35             | Swivel      | 108mm         | 76mm             | 12mm       | 75mm       | SS-80-GVR/BH12<br>70Kg   | SS-80-PNB/BH12*<br>70Kg  | SS-80-NY/BH12<br>70Kg    | SS-80-TH/BH12<br>70Kg   | -                      |
| 4" 100mm    | GVR = 23<br>PNB = 30<br>NYB = 34<br>TH = 35<br>HT = 34 | Swivel      | 128mm         | 76mm             | 12mm       | 85mm       | SS-100-GVR/BH12<br>80Kg  | SS-100-PNB/BH12<br>80Kg  | SS-100-NYB/BH12<br>80Kg  | SS-100-TH/BH12<br>80Kg  | SS-100-HT/BH12<br>80Kg |
| 5" 125mm    | GVR = 23<br>PNB = 30<br>NYB = 38<br>TH = 35            | Swivel      | 155mm         | 70mm             | 12mm       | 105mm      | SS-125-GVR/BH12<br>100Kg | SS-125-PNB/BH12<br>100Kg | SS-125-NYB/BH12<br>100Kg | SS-125-TH/BH12<br>100Kg | -                      |

\* The 80mm Polyurethane wheel is grey on grey

## OPTIONAL EXTRA



### Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add 'suffix **'SWB'** to the swivel castor reference.

### Swivel Radius

The swivel radius is increased when brakes are fitted.

- 80mm wheels: increased by 45mm
- 100mm wheels: increased by 40mm
- 125mm wheels: increased by 30mm