

Medium Duty Bolt Hole Stainless Steel Castors



SS Series Stainless Steel Swivel Castors

Size: 80mm, 100mm & 125mm

Our medium duty Stainless steel bolt hole castors range are ideal for use in clean rooms and a range of environments. Available in sizes 80mm, 100mm and 125mm with a range of wheels including rubber, polyurethane, nylon and both high temperature termotex and high temperature rubber. Ideal for food processing, institutional and hospital equipment industries. Can be supplied braken or un-braked.

Castor Reference and Load Capacity

Wheel Diam.	Tread width (mm)	Castor Type	Castor Height	Swivel Race Diam	Bolt Diam.	Swiv. Rad.	Grey Rubber	Polyurethane	White Nylon	High Temp Termotex	High Temp Rubber
3" + 80mm	GVR = 27 PNB = 38 NY = 34 TH = 35	Swivel	108mm	76mm	12mm	75mm	SS-80-GVR/BH12 70Kg	SS-80-PNB/BH12* 70Kg	SS-80-NY/BH12 70Kg	SS-80-TH/BH12 70Kg	-
4" 100mm	GVR = 23 PNB = 30 NYB = 34 TH = 35 HT = 34	Swivel	128mm	76mm	12mm	85mm	SS-100-GVR/BH12 80Kg	SS-100-PNB/BH12 80Kg	SS-100-NYB/BH12 80Kg	SS-100-TH/BH12 80Kg	SS-100-HT/BH12 80Kg
5" 125mm	GVR = 23 PNB = 30 NYB = 38 TH = 35	Swivel	155mm	70mm	12mm	105mm	SS-125-GVR/BH12 100Kg	SS-125-PNB/BH12 100Kg	SS-125-NYB/BH12 100Kg	SS-125-TH/BH12 100Kg	-

* The 80mm Polyurethane wheel is grey on grey

OPTIONAL EXTRA



Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add 'suffix **'SWB'** to the swivel castor reference.

Swivel Radius

The swivel radius is increased when brakes are fitted.

80mm wheels: increased by 45mm

100mm wheels: increased by 40mm

125mm wheels: increased by 30mm