

# Medium Duty Flat Top Plate Stainless Steel Castors



**SS Series** Stainless Steel Swivel Castors  
Size: 80mm, 100mm, 125mm, 160mm & 200mm

**SF Series** Stainless Steel Fixed Castors  
Size: 80mm, 100mm, 125mm, 160mm & 200mm

STAINLESS STEEL SWIVEL & FIXED CASTORS have been introduced to cater for the increased demand in the food processing, institutional and hospital equipment industries.

## Castor Reference and Load Capacity



Wheel Diam.	Tread width (mm)	Castor Type	Castor Height	Plate size (mm)	Bolt Hole spacing (mm)	Bolt Diam.	Swiv. Rad.	Grey Rubber	Polyurethane	White Nylon	High Temp Termotex	High Temp Rubber
3" + 80mm	GV=27 PN=38 NY=34 TH=35	Swivel	108mm	105 x 85	80 x 60	8mm	75mm	SS-80-GVR 70kg	*SS-80-PNB 100kg	SS-80-NY 100kg	SS-80-TH 100kg	-
		Fixed	108mm	99 x 85	80 x 60	8mm	-	SF-80-GVR 70kg	*SF-80-PNB 100kg	SF-80-NY 100kg	SF-80-TH 100kg	-
4" 100mm	GV=23 PN=30 NY=34 TH=35 HT=34	Swivel	128mm	105 x 85	80 x 60	8mm	85mm	SS-100-GVR 80kg	SS-100-PNB 150kg	SS-100-NYB 150kg	SS-100-TH 125kg	SS-100-HT 60kg
		Fixed	128mm	101 x 85	80 x 60	8mm	-	SF-100-GVR 80kg	SF-100-PNB 150kg	SF-100-NYB 150kg	SF-100-TH 125kg	SF-100-HT 60kg
5" 125mm	GV=23 PN=30 NY=38 TH=35	Swivel	155mm	105 x 85	80 x 60	8mm	105mm	SS-125-GVR 100kg	SS-125-PNB 300kg	SS-125-NYB 300kg	SS-125-TH 150kg	-
		Fixed	155mm	101 x 85	80 x 60	8mm	-	SF-125-GVR 100kg	SF-125-PNB 300kg	SF-125-NYB 300kg	SF-125-TH 150kg	-
6" + 160mm	PN=40 NY=40 TH=40	Swivel	196mm	140 x 110	105 x 80/75	10mm	140mm	-	SS-160-PNB 350kg	SS-160-NY 350kg	SS-160-TH 250kg	-
		Fixed	196mm	140 x 110	105 x 80/75	10mm	-	-	SF-160-PNB 350kg	SF-160-NY 350kg	SF-160-TH 250kg	-
8" 200mm	PN=50 NY=46 TH=40	Swivel	236mm	140 x 110	105 x 80/75	10mm	165mm	-	SS-200-PNB 400kg	SS-200-NY 400kg	SS-200-TH 300kg	-
		Fixed	236mm	140 x 110	105 x 80/75	10mm	-	-	SF-200-PNB 400kg	SF-200-NY 400kg	SF-200-TH 300kg	-

\*The 80mm Polyurethane wheel is grey on grey.

## OPTIONAL EXTRA



### Combined Swivel and Wheel Brake (all sizes)

Foot operated wheel brake simultaneously brakes both the swivel head and wheel. Release is affected by the trip pedal. To order add suffix 'SWB' to the swivel castor reference.

### Swivel Radius

The swivel radius is increased when brakes are fitted.  
80mm wheels: increased by 45mm  
100mm wheels: increased by 40mm  
125mm wheels: increased by 30mm  
160mm wheels: increased by 30mm  
200mm wheels: increased by 30mm